

Datasheet

1000 C ZII Containerised Zone II Air Compressor

As a rental option the Rentair Offshore Zone II containerised compressors are ideal for operations such as well testing and oilfield applications in hazardous areas.

The compact footprint, containerised housing, and forklift slots make it easy and cost efficient to transport, whilst easy stacking ability further reduces use of deck space onsite. The internal access provides offshore personnel with safe operational and servicing capability.

Rentair Offshore Zone II compressors range from 750cfm to 1050cfm all with 590 litre fuel tanks for up to 10 hours of operation at full load, resulting in maximised operational time. Customers benefit from latest Zone II technology, for operation in hazardous areas, heavy duty DNV 2.7-1 specification and reduced downtime with optional 24/7 support from Rentair Offshore Service Technician Team.



Features:

- Rugged, reliable marine engine with high ambient cooler design
- Heavy duty, fully bunded, DNV2.7-1 offshore container
- Designed for Zone II hazardous area operation
 - BP200, OCMA Mec1, EEMUA 107
- Designed for offshore stacking
- Internal personnel access way between units when stacked
- Exhaust gas cooling, inlet shut down and flame trap
- All pneumatic starting, control and tell-tale fault indication
- Compact design - transport three framed in a 40ft shipping container
- Emergency shut down and refuelling from deck level

Options:

- Aftercooler, filtration, drying
- Extra high ambient cooling package
- Dummy flame traps
- 'Yellow alert' shut down connection - 24V and 110V (others)
- CE marked and fully ATEX compliant (EN1834-1)
- Experienced offshore service technician(s) for operational and maintenance assistance

Technical Specifications

1000 C ZII Containerised Zone II Air Compressor

Performance

Flow	1050 cfm 29.73 m3/min
Working Pressure	125 PSIG 8.61 barg
Fuel Tank	590 litres
Fuel Consumption	62 litres/hr
Full Load Running	9.5 hours
Ambient Operating Temperatures	-10°C / 45°C
Noise at full load	111dba
Vibration at full load	0.87mm/s
Start system	Pneumatic
Safety system	Electro / Pneumatic

Lifting Specification, Weights & Dimensions

Lifting Spec	DNV 2.7-1
Length	3990 mm
Width	2250 mm
Height	2210 mm
Weight (kg dry)	8,100kgs
Weight (kg op)	8,200kgs
Max Gross weight	10,000kgs
Shipping Weight	8,200 / 8,500kgs

Safety Features

External Emergency Stop	2 x Push Button
Internal Emergency Stop	1 x Push Button
Internal Lighting	110 volt with emergency battery back up
Exhaust Manifold	Water Cooled
Exhaust Turbocharger	Water Cooled
Rig ESD Connection	Electro / Pneumatic
Scramble Net	Stacked Escape System

Engine Specification

Engine model	Caterpillar 3306 DITA
Power Output at Flywheel	320hp / 230kw
Engine idle speed	1200/1500rpm
Maximum engine speed	2100rpm
Engine oil capacity	28 Litres
Engine oil specification (minimum)	15w40 Mineral
Engine coolant capacity	200litres
Fuel consumption at full load	65litres per hour
Fuel specification	Gas Oil (BS2869 Class A2&D)
Maximum thermal input	659kw
Rated thermal efficiency	0.35
Exhaust temperature	<196°C
Cooling pack outlet temperature	38°C @ ambient of 3°C

Compressor Performance

Type	Oil Flooded Screw
Output	1050cfm
Maximum operating pressure	150psi
Lubrication oil capacity	85litres
Lubrication oil specification	Dexron II Automatic Transmission Fluid - Mineral

Operating Systems

Start system air supply	115psi - 150psi
Start air supply	680cfm (maximum)
Safety system shutdowns	Pneumatic
Compressor discharge	2 x 2" & 2 x 3/4" Ball Valves
Air Start Connection	1 x 3/4" Crowsfoot
ISO Interlockers	Positive Lock
Stacked Access	Internal System

For more information on Air Compressors please contact your local Rentair Offshore representative or email offshore@rentairoffshore.com

Note: The above referred specifications are our minimum standard and for guidance purposes only. For compressor specific information applicable to comply with region specific standards please consult your local Rentair Offshore representative.

Aberdeen, UK
+44(0)1224 215400

Great Yarmouth, UK
+44 (0)1493 656003

Netherlands
+31 (0)223 630 552

Singapore
+65 3125 2312